

Produkt - splitt varmepumpe

Outdoor unit	Singelsplitt inverter	RAS-25J2AVG-ND
Indoor unit	SEIYA R32	RAS-25J2KVG-ND

Function

Cooling	Y
Oppvarming - gjennomsnittlig	Y
Oppvarming - Varmere	N
Oppvarming - Kaldere	N

Design load

Cooling	Pdesignc	2.5	kW
Heating/Average	Pdesignh	2.8	kW

Capacity control = Variable

Årsvarmefaktor eller SCOP

Cooling	SEER	6.50	A++
Heating/Average	SCOP(A)	4.60	A++

Cooling

Kapasitet

Declared capacity for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Effektivitet

Declared Energy efficiency ratio for cooling at indoor temperature 27(19)°C and outdoor temperature Tj.

Tj=35°C	Pdc	2.50	kW	Tj=35°C	EERd	3.99
Tj=30°C	Pdc	1.84	kW	Tj=30°C	EERd	5.90
Tj=25°C	Pdc	1.18	kW	Tj=25°C	EERd	8.20
Tj=20°C	Pdc	1.04	kW	Tj=20°C	EERd	10.20

Oppvarming (gjennomsnittsklima)

Kapasitet

Declared capacity for Heating/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Effektivitet

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj.

Tj=-7°C	Pdh	2.54	kW	Tj=-7°C	COPd	2.97
Tj=2°C	Pdh	1.52	kW	Tj=2°C	COPd	4.75
Tj=7°C	Pdh	1.09	kW	Tj=7°C	COPd	5.86
Tj=12°C	Pdh	1.10	kW	Tj=12°C	COPd	6.87
Tj=bivalent temperature	Pdh	2.80	kW	Tj=bivalent temperature	COPd	2.76
Tj=driftsbegrensning	Pdh	1.77	kW	Tj=driftsbegrensning	COPd	2.00
Bivalent temperature		-10	°C			
Laveste utetemperatur for drift		-20	°C			

Elektrisitet

Electric power input in power modes other than "on mode"

Sesonggjennomsnittlig tilført elektrisk energi

off mode	Poff	0.001	kW	Cooling	QCE	133	kWh/a
standby mode	Psb	0.001	kW	Heating/Average	QHE/A	850	kWh/a
thermostat-off mode	Pto	0.044	kW	Heating/Warmer	QHE/B	x	kWh/a
crankcase heater mode	Pck	0.000	kW	Heating/Colder	QHE/C	x	kWh/a

Kuldemedium

Type		R32					
Vekt				0.67	kg		
Globalt oppvarmingspotensial	GWP			675	kgCO ₂ eq.		

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAS-25J2AVG-ND	63	64	RAS-25J2AVG-ND	32	32
RAS-25J2KVG-ND	56	57	RAS-25J2KVG-ND	12	12

Dimensjoner

	Høyde	Bredde	Dybde	Vekt
RAS-25J2AVG-ND	550 mm	780 mm	290 mm	30 kg
RAS-25J2KVG-ND	293 mm	798 mm	230 mm	10 kg

Harmonisert standard	EN14511:2007, EN12102
----------------------	-----------------------

Kalkulasjonsmetode - målestandard	PrEN 14825: 2011 Kapittel 8 og 9
-----------------------------------	----------------------------------

Kontakt for mer informasjon	Importør/distributør i EU: Toshiba Carrier UK Ltd. Porsham Close, Belliver Industrial Estate, PLYMOUTH, Devon, PL6 7DB. United Kingdom
-----------------------------	--

Supplier	TOSHIBA CARRIER CORPORATION
----------	-----------------------------

Innedel	RAS-25J2KVG-ND
---------	----------------

Utedel	RAS-25J2AVG-ND
--------	----------------

Sound power level

innedel (kjøling)	dB	56
-------------------	----	----

utedel (kjøling)	dB	63
------------------	----	----

innedel (oppvarming)	dB	57
----------------------	----	----

utedel (oppvarming)	dB	64
---------------------	----	----

Kuldemedium

Type		R32
------	--	-----

Globalt oppvarmingspotensial	kgCO ₂ eq	675
------------------------------	----------------------	-----

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling

Energy efficiency class		A++
-------------------------	--	-----

Design load (P _{designc})	kW	2.5
-------------------------------------	----	-----

Årsvarmefaktor eller SCOP (SEER)		6.50
----------------------------------	--	------

Sesonggjennomsnittlig tilført elektrisk energi (Q _{CE})	kWh/annum	133
---	-----------	-----

Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A++	x	x
Design load (Pdesignh)	kW	2.8	x,x	x,x
Årsvarmefaktor eller SCOP (SCOP)		4.60	x,xx	x,xx
Sesonggjennomsnittlig tilført elektrisk energi (Q _{HE})	kWh/annum	850	x	x
Back-up varmekapasitet	kW	0.00		
Spesifisert varmekapasitet ved innetemperatur 20 °C og utetemperatur Tj.				
Tj= -7°C (Pdh)	kW	2.54	-	x,xx
Tj= 2°C (Pdh)	kW	1.52	x,xx	x,xx
Tj= 7°C (Pdh)	kW	1.09	x,xx	x,xx
Tj= 12°C (Pdh)	kW	1.10	x,xx	x,xx
Tj=bivalent temperature (Pdh)	kW	2.80	x,xx	x,xx
Tj=driftsbegrensning (Pdh)	kW	1.77	x,xx	x,xx
Tj= -15°C (Pdh)	kW	-	-	x,xx